



Ref. Certif. No.

DE1-68964

IECEE CBTC

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Power supply for IT-Equipment / DC/DC-Converter

Name and address of the applicant

OmniOn Power Inc.
601 Shiloh Road
Plano TX 75074
United States of America

Name and address of the manufacturer

OmniOn Power Inc.
601 Shiloh Road
Plano TX 75074
United States of America

Name and address of the factory

Flextronics Electronics Technology (Suzhou) Co., Ltd.
No. 9 Sugian Road China-Singapore
Suzhu Industrial Park
215021 SUZHOU
Jiangsu
China

Note: When more than one factory, please report on page 2

Additional Information on page 2

Ratings and principal characteristics

Input: DC 36-75 V, max. 19 A, Output: DC 5-13,2 V or DC 12 V, max. 50 A

Trademark / Brand (if any)

OmniOn Power Inc.

Customer's Testing Facility (CTF) Stage used

CTF Stage 3

Model / Type Ref.

QSDW035A0X, QSVW035A0X, QSDW042A0X,
QSVW042A0X, QSDW050A0X, QSVW050A0X

This CB Test Certificate is issued by the National Certification Body

VDE Prüf- und Zertifizierungsinstitut GmbH
Zertifizierungsstelle und internat. Angelegenheiten
Certification Body and internat. Affairs

Date: 2024-08-23

Signature:

G. Heine



Ref. Certif. No.

DE1-68964

Additional information (if necessary may also be reported on page 2)

A sample of the product was tested and found to be in conformity with

As shown in the Test Report Ref. No. which forms part of this Certificate

Additional Information on page 2

IEC 62368-1:2018

317363-TL6-1

Additional factories

OmniOn Power Shanghai Co., Ltd.
No.1353 Chen Qiao Rd.
Fengpu Industrial Park
201401 Shanghai
Shanghai
China

Additional information

1. Special suffix SxRx - Denotes a special model where output voltage is factory adjusted per customer request, as follows:
Example: Output voltage suffix = S9R0, S = Special, 9R0 = 9.0 volts
2. 'X' represents optional alpha-numeric characters defining non-safety affecting characteristics, such as mounting holes, pin length, remote ON-OFF, customer identification, etc.
The optional suffixes may be separated by a dash (e.g. - QSVW035A0B61-HZ).
See below for a partial list of optional non-safety affecting suffixes.

Suffix:

Output voltage = B, Negative remote on/off logic = 1, Auto-restart = 4, Pin Length (0.145 in) = 6, Surface-Mount Version = S, Heat plate Versions = H, Rohs Compliant = Z, Active Load Sharing (parallel operation) = P

This CB Test Certificate is issued by the National Certification Body

VDE Prüf- und Zertifizierungsinstitut GmbH
Zertifizierungsstelle und internat. Angelegenheiten
Certification Body and internat. Affairs

Date: 2024-08-23

Signature:

G. Heine